Wireless monitor with inbuilt remote control of ARRI's Alexa-Mini & AMIRA cameras

StarliteRF-a

Video input & output	1 x 3G/HD/SDI
Supported standards	HD: 1080 / 50i, 60i 1080 / 24p, 25p, 30p, 24psf, 25psf, 720 / 25p, 30p, 50p, 60p
Display type & size	AMOLED - 5 inches
Pixels	Picture zone 1280 x 720
Contrast ratio	3400:1
Viewing angle	±170° H & V
Brightness max	380 Nits
Color temperature	D56
Avenger Leveler	yes
Power	6 to 30V DC (-1, +2) Lemo2 mini (EGG.0B.302 CLL)
Power cons.	12W
Battery socket	Sony type L
Built-in receiver frequency	5.8GHz ISM band
Dimensions (W x H x D)	144 x 128 x 40 mm 5,66 x 5,03 x 1,57 inches
Weight	350g / 0.77 lbs

Key strengths

- Small and lightweight.
- Robust connection with TitanHD2 TX-a within a range of 200 meters LOS.
- Visibility in a bright environment.
- Ability to record dailies in H264 on to SD card.

Reliable

The wireless incorporates video transmission with 0 delay, low loss and no latency

Ergonomic

Small, lightweight and fits easily in the palm of your hand or mounted on top of remote hand units.



The Only 5" OLED touch-screen, monitor-recorder with a built-in wireless receiver.





The Starlite**RF-a** is the first all-in-one 5" OLED touch-screen, monitor recorder with a built-in wireless receiver.

Free of cables, lightweight and with all the reliability, accuracy and fine engineering that Transvideo build into their products, it is the perfect choice for directors, assistant directors, focus pullers and DOPs. It can also directly remote Arri's camera Alexa or AlexaMini.