

Starlite RF-a

Wireless monitor with inbuilt remote control of ARRI's Alexa-Mini & AMIRA cameras



Based on the **Starlite HDs** core technologies, the new **Starlite RF** is the first all-in-one 5" OLED touch-screen, monitor-recorder with a built-in wireless receiver.

Small and lightweight, it operates on the 5.8GHz ISM band, has a top mounted antenna and a Sony prosumer battery connection at the back.

Free of cables, lightweight and with all the reliability, accuracy and fine engineering that Transvideo build into their products, it is the perfect choice for directors, assistant directors, focus pullers and DOPs.

Key strengths

- Small and lightweight.
- Robust connection with **Titan HD2** within a range of 200 meters LOS, distance might be affected by other transmission &/or environment.
- Visibility in a bright environment.
- Ability to record dailies in H264 onto SD card.

Reliable

Top class wireless transmission system with a range of 200m/600ft.

The wireless incorporates video connectivity without latency, with low loss and without any transmission delay.

Ergonomic

Small, lightweight and fits easily in the palm of your hand or mounted on top of remote hand units.

Unique

The Only 5" OLED touch-screen, monitor-recorder with a built-in wireless receiver.



Specifications

Video input / output	1 x 3G/HD/SDI
Supported standards	3G: 1080 / 50p, 60p HD: 1080 / 50i, 60i 1080 / 24p, 25p, 30p, 24psf, 25psf, 720 / 25p, 30p, 50p, 60p
Display type & size	AMOLED - 5 inches
Pixels	Picture zone 1280 x 720
Contrast ratio	3400:1
Viewing angle	±170° H & V
Brightness max	380 Nits
Color temperature	D56
Avenger Leveler™	yes
Power	6 to 30V DC (-1, +2) Lemo2 mini (EGG.0B.302 CLL)
Power cons.	12W
Battery socket	Sony type L
Built-in receiver frequency	5.8GHz ISM band
Dimensions (w x h x d)	144 x 128 x 40 mm 5,66 x 5,03 x 1,57 inches
Weight	350g / 0.77 lbs